



# 1, 2, 3 ACTION!

### For your trucks, loaders, MANITOU makes your tyre

### **SAFER**

- Visibility, best panoramic view on the market
- Fall back protection arms to avoid tyres falling off and crushing personnel
- Maneuverability of the equipment with intuitive controls
- Continuous monitoring of the machine stability
- Movements combination avoiding unnecessary machine manoeuvres, while changing a tyre.
   Only the clamp and the tyre moves, not the machine





| THE WIDEST RANGE OF THE MARKET |                        |   |                       |                 |                 |               |
|--------------------------------|------------------------|---|-----------------------|-----------------|-----------------|---------------|
| Name                           | Max Capacity<br>kg Lbs | Opening range<br>(Min / Max)<br>mm <i>Ft,In</i> | Side Shift            | Body Rotation   | Pads Rotation   | Design Type   |
| TH K 1000                      | 1000<br><i>2200</i>    | 560 mm / 2060 mm<br>23" / 81"                   | +/- 100 mm<br>+/- 3"  | 360° Continuous | None            | Flat Clamp    |
| TH <b>K 2000</b>               | 2000<br><i>4400</i>    | 560 mm / 2190 mm<br>23" / 86"                   | +/- 100 mm<br>+/- 3"  | 360° Continuous | None            | Flat Clamp    |
| TH <b>49</b>                   | 2500<br><i>5500</i>    | 1100 mm / 3400 mm<br>43"/133"                   | +/- 150 mm<br>+/- 5"  | +/- 22,5 °      | 0°-120°         | Telescopic    |
| TH <b>51</b>                   | 3500<br><i>7700</i>    | 1130 mm / 3410 mm<br>44"/134"                   | +/- 150 mm<br>+/- 5"  | +/- 22,5 °      | 0°-120°         | Parallelogram |
| TH <b>57</b>                   | 6000<br><i>13200</i>   | 1210 mm / 3830 mm<br>47" / 150"                 | +/- 300 mm<br>+/- 11" | +/- 172°        | 360° Continuous | Parallelogram |
| TH <b>63</b>                   | 9300<br><i>20500</i>   | 1580 mm / 4170 mm 62"/ 164"                     | +/- 300 mm<br>+/- 11" | +/- 172°        | 360° Continuous | Telescopic    |
| *TH <b>63+</b>                 | 12000<br><i>26400</i>  | 600 mm / 4200 mm<br>23" / 165"                  | +/- 300 mm<br>+/- 11" | +/- 172°        | 360° Continuous | Parallelogram |

### maintenance...

How can we easily improve the safety and efficiency of my tyre maintenance?



## COST EFFICIENT

- Versatility of the MANITOU Telescopic Handler to diversify your return of investment through multiple attachment solutions
- Production equipment back to work quicker
- Improves your maintenance fleet management by **decreasing the number of equipment**
- Enhances maintenance schedule flexibility

### **MORE PRODUCTIVE**

- Change your tyres anywhere anytime
- Rough terrain ability: permanent 4WD 4 wheel steer with switchable steering modes
- **Full hydraulic power** dedicated to the attachment movements
- As versatile as a human wrist. **Up to 8 combined movements**









### **THE Material Handling Reference**

Your nearest dealer:

#### A full line of attachments for the Mining Industry

Cylinder Handlers Tyre Handlers

Jibs Man Baskets Buckets Hooks Winchs



